Author Index

Beck, V. R., 121
Blythe, A., 37
Bøhm, B., 103

Eckhoff, R. K., 153
Ehm, C., 109
Emmons, H. W., 183

Goodsman, R. W., 37

Haksever, A., 109
Hansell, G. O., 9
Harmathy, T. Z., 75
Hartzell, G. E., 179

Kanury, A. M., 65
Kirby, B. R., 139

Latham, D. J., 139
Law, M., 85

Mason, F., 37
Mehaffey, J. R., 75
Melinek, S. J., 1
Morgan, H. P., 9, 83
Mudan, K. S., 89
Musse Rasmussen, B., 103

Nelson, H. E., 167
Newman, J. S., 205

Pauls, J., 213
Pedersen, G. H., 153

Theobald, C. R., 51
Thomas, P. H., 1, 191
Thomson, G., 139

Watts, J. M., Jr., 237
Weckman, H., 97

© Elsevier Sequoia/Printed in The Netherlands

Fire Safety Journal, 12 (1987) 248 - 249

Subject Index

Atrium buildings
  calculating smoke flows in atria for smoke-control design, 9

Bearing members
  biaxial concrete data for, under fire attack, application of, 109
Building fire safety and protection
  cost-effective, decision-making model for, 121

Computer models
  for evacuation analysis, 237
Concrete data
  for bearing members under fire attack, application of biaxial, 109

Evacuation analysis
  computer models for, 237
Evacuation times
  for tall buildings, calculating, 213
Experimental natural fires
  temperatures attained by unprotected structural steelwork in, 139
Explosibility
  of peat dust, measurements of, 97

Far field effects
  analysing, 183
Fire(s)
  experimental natural, temperatures attained by unprotected structural steelwork in, 139
  housing factors and, in two metropolitan boroughs, 37
  in multi-level shopping malls, a note on smoke plumes from,
    comments on, 83
    reply to comments on, 85
Fire attack
  application of biaxial concrete data for bearing members under, 109
Fire compartment
  development of small-scale, in order to determine thermal exposure inside and outside buildings, 103
Fire detector response
  prediction of, 205
Fire safety and protection
  cost-effect, decision-making model for building, 121

Geometric view factors
  for thermal radiation hazard assessment, 89

Grain dust explosions
  initiation of, by heat generated during single impact between solid bodies, 153

Hazard assessment
  thermal radiation, geometric view factors for, 89
Heat flow
  to insulated steel, 1
Heat load concept
  normalized, and its use, 75
Housing factors
  and fires in two metropolitan boroughs, 37

Life safety analysis
  concepts for, 167

Modeling
  in engineering and science, on the craft of, 65

Peat dust
  measurements of explosibility of, 97
Prediction
  of fire detector response, 205

Shopping mall(s)
  a note on smoke plumes from fires in multi-level
    comments on, 83
    reply to comments on, 85
  problems, on upward movement of smoke and related, 191
Smoke
  on upward movement of, and related shopping mall problems, 191
Smoke-control design
  atrium buildings; calculating smoke flows in atria for, 9
Smoke flows
  calculating, in atria for smoke-control design; atrium buildings, 9
Smoke plumes
  from fires in multi-level shopping malls, a note on,
    comments on, 83
    reply to comments on, 85
Sprinklers
  thermal response of; FRS heated wind tunnel, 51
Steel
  heat flow to insulated, 1
Steelwork
  temperatures attained by unprotected structural, in experimental natural fires, 139

Tall buildings
  calculating evacuation times for, 213
Temperatures
  attained by unprotected structural steelwork in experimental natural fires, 139

© Elsevier Sequoia/Printed in The Netherlands

Thermal exposure
development of small-scale fire compartment in order to determine, inside and outside buildings, 103
Thermal radiation
hazard assessment, geometric view factors for, 89
Thermal response
of sprinklers; FRS heated wind tunnel, 51
Toxic hazard
criteria and methods for evaluation of, 179

Wind tunnel
FRS heated; thermal response of sprinklers, 51